

Helena Township
27466 Delmar Avenue
New Prague, MN 56071

Name of Applicant: _____

Present Address: _____

Address of New Driveway: _____

Home phone #: _____

Day phone #: _____

Completed by Helena Township Road Overseer

Permit # _____

1. No driveway construction until approved by Road Overseer Darryl Perkins (952.758.3973)
2. All culverts will be a minimum of 15" new galvanized steel. Road Overseer will determine if larger culvert is needed. Length varies from 26' to 30'.
3. Owner of the driveway is responsible for cleaning and maintaining culvert.
4. Minimum driveway width of 20'; maximum width of 28' where driveway meets township road; aprons recommended.
5. To ensure all water shed flows away from township road, there must be a 6" slope 15' from edge of road surface (not road ROW)
6. It is illegal to erect any retaining structures, decorative posts, etc. within township ROW. Township is not responsible for damage to mailboxes and posts during road maintenance.
7. A non-refundable fee of \$400.00 will be collected at the time of application; the fee includes an installed mailbox breakaway post. Field approaches require a non-refundable fee of \$150.00.
8. Culvert ends will have a 6:1 slope; headwalls are not allowed within the road ROW.
9. Non-platted driveways are to be a minimum of 300' from any existing driveway; platted driveways must be 35' from side property lines.
10. One driveway allowed per lot; corner lots may have a second driveway from a different township road upon township pre-approval.
11. Seed or sod all ditches.
12. Dirt/debris are not allowed on township roads.
13. Driveway must be built and graveled before construction of the home or any other building begins.
14. If any portion of the driveway is damaged during road maintenance, the township is not liable.
15. **Notification of Road Overseer, Darryl Perkins at 758-3973 upon completion of work.**

Date

Township of Helena

Additional Comments or Instructions:

